

**6-Stage torque adjustment** for a wide range of applications.

**Removable front cap** for changing from self-drilling screws to hex bolt operation.

**Ingenious exhaust vents** designed so that exhaust air does not blow dust and debris around when operating close to floor level.

**Reversing switch lever** enables changing rotation direction with one hand.

Variable speed control Increased pressure on the trigger switch increases the rotational speed.

LED job light convenient for operation in dark job sites.



### Bit holder for spare bit storage.

Rubberized soft grip provides comfortable grip and more control, while minimizing operator fatigue.

### **MAKITA ADVANTAGE**

For effectively driving

6-Stage torque adjustment for a wide range of applications. Compact design, well balanced for easy handling and maneuverability. Easy to bring pressure in line with center of driving bit axis. First corded screwdrivers equipped with LED job light.

## SPECIFICATIONS

Application a variety of screws Capacities Drywall screw Self drilling screw Hex screw Driving shank Continuous rating input No load speed Overall dimensions L x W x H Net weight Power supply cord Carbon brush

### **FEATURES:**

Double insulation, variable speed, reversing, torque setting 6 & built-in job light

6mm

6mm

6mm

570W 0 - 2 500r/min

1.8kg

2.5m

CB419

6.35mm hex

301 x 70 x 192mm



# FS2700

# **Screwdriver**

makita

2500

### Belt clip

more durable, comprising sheet metal sandwiched between plastic layers for added strength.

570W

### Tool Body

Best possible ergonomic design for screwdriving : • minimizes operator fatigue

- minimizes operator fatigue even when used continuously for long periods.
- gives maximum power thrust.
  allows for much smoother
- and easier trigger pull

